



19" 1U Rack Mount TFT Console

Features:

- Single Rail easy to install and use
- Supports 15 various keyboard languages
- Bright Active Matrix TFT Display
- OSD function (On Screen Display) for LCD display
- Durable keyboards (touchpad or trackball)
- Panel protected by tempered glass
- Support USB K/B, touchpad (optional)
- Audio Function (optional)
- DC power (optional)
- Support DVI (optional)



Specification

Model Number	PL190U-RM-XAXR
Display Size	19"
Dimension	447.5 x 532 x 44mm / 17.6 x 20.9 x 1.7in
Net Weight	13.0Kg / 28.7Lb
Panel Type	Active Matrix TFT LCD
Resolution	Maximum Resolution up to 1280X1024
Pixel Pitch	Supports 0.298mm x 0.294mm
Viewing Angle	Right-Left view 140°(Typ) Up-Down view 140°(Typ)
Contrast Ratio	500:1
Brightness	White 250cd/m2 (Center 1 point Typ)
Back Light	Four Lamps for Back Light
Supported Colors	16.2M Colors (6-bit with FRC)
Response Time	Rising Time 2ms, Decay Time 14ms
Operating System	Dos, Windows (3.1, 9x, 2000, NT4, ME, XP, 2003 Server) Linux, Novell 3.12-6, HP UX, SUN
System Cables	VGA+2xPS/2 cable
Keyboard Mouse	106 key PS/2 keyboard with touch pad
Sync	45~80KHZ
Power Source	100-240 VAC input
Power Consumption	25W, 21.05W for Panel
Temperature	Operate 0°~ 50°C / 32°~ 122°F, Storage-20°~ 60°C / -4°~ 140°F
Humidity	10%~90%RH
Keyboard Language	Standard USA, Options for (UK, German, French, Spanish, Italian, Portuguese, Dutch, Swiss, Belgium, Swedish, Norwegian, Danish, Japan, Taiwan)
Certification	CE/FCC, UL/CUL/C-Tick

